

Gestetner

TOTAL DOCUMENT SOLUTIONS



DSm615/618/618d



FOUR DIFFERENT
DOCUMENT DEMANDS, ONE
COMPACT SOLUTION

Aficio™

SPECIFICATIONS

DSm615/DSm618/DSm618d

Copier

Copying process

Twin laser beam scanning and electro-photographic printing

Copy speed

15/18 copies per minute

Resolution

600dpi

Multiple copy

Up to 99

Warm-up time

Less than 15 seconds

First output speed

Less than 6.5 seconds

Zoom

50-200% (in 1% steps)

Memory

Standard: 16MB

Paper input capacity

Standard:

DSm615: 250-sheet paper tray

DSm618/DSm618d:

2 x 250-sheet paper trays

Maximum:

DSm615: 1,350 sheets

DSm618/DSm618d: 1,600 sheets

Paper output capacity

Standard: 250 sheets (internal tray)

Paper size

Standard tray: A5-A3

Bypass tray: A6-A3

Duplex unit: A5-A3

Paper weight

Standard tray: 60-90g/m²

Bypass tray: 52-162g/m²

Duplex unit (DSm618d): 64-90g/m²

Dimensions (W x D x H)

DSm615: 550 x 568 x 420mm

DSm618: 550 x 568 x 558mm

DSm618d: 587 x 568 x 558mm

Weight

DSm615: Less than 35kg

DSm618: Less than 44kg

DSm618d: Less than 47kg

Power source

110-120V, 220-240V, 50/60Hz

Power consumption

Operation: Less than 1.28kW

Energy saver mode: Less than 40W

Printer (Option)

Print speed

15/18 prints per minute

Printer language/resolution

Standard: PCL5e: 300/600dpi

PCL6: 600dpi

RPCS™: 300/600dpi

Option:

Adobe® PostScript® 3™: 600dpi

Interface

Standard:

Ethernet 10 base-T/100 base-TX, USB2.0

Option:

Bi-directional IEEE1284 parallel port

Wireless LAN (IEEE802.11b)

Bluetooth

IEEE1394

Memory

Standard: 192MB

Network protocol

TCP/IP, IPX/SPX, NetBEUI, AppleTalk

Supported Environments

Windows®

95/98/Me/NT4.0/2000/XP/2003 Server

Macintosh 8.6 or later (except for v10.0.X)

Unix/Linux

IBM iSeries /AS/400® using OS/400 Host

Print Transform

Netware 3.12/3.2/4.1/4.11/5.0/5.1/6

Scanner (Option)

Scan speed

Maximum 43 originals per minute (MH, A4)

Resolution

600dpi

Original size

A5-A3

Output formats

PDF/TIFF

Bundled drivers

Network TWAIN

Scan-to-Email

SMTP and TCP/IP required

Destination addresses

Maximum 100

Stored destination addresses

Maximum 150

Address book

Via operation panel, Web Image Monitor or SmartDeviceMonitor™

Fax (Option)

Circuit

PSTN, PBX

Compatibility

ITU-T (CCITT) G3

Modem speed

Maximum 33.6Kbps

Resolution

200 x 200/100/400dpi

Compression method

MH, MR, MMR, JBIG

Scanning speed

1 second (200 x 200dpi, A4, SEF)

Memory capacity

Standard: 3MB

Memory backup

Yes

Software

SmartDeviceMonitor™¹

Web SmartDeviceMonitor™

Web Image Monitor

DeskTopBinder™ V2 Lite¹

ScanRouter™ V2 Lite¹

¹ Bundled with printer/scanner option

Other Options

- Platen cover
- 30-sheet automatic document feeder
- 50-sheet automatic reverse document feeder (DSm618d)
- 100-sheet one-bin tray (DSm618/DSm618d)
- 1 x 500-sheet paper tray
- 2 x 500-sheet paper trays
- Cabinets

All Gestetner products conform to the ISO9001 quality and ISO14001 environmental management system standards, throughout every stage of manufacture.

We reserve the right to make amendments to the technical specifications and external appearance of this equipment. Please note that the full range of options shown in this publication may not always be available. All brand and product names are recognized and hereby acknowledged, as registered trademarks of their respective owners.



Gestetner

Part of the NRG group

www.gestetner.com

