



DSm725/DSm730



SPECIFICATIONS

DSm725/D5m730

Printer (Option)

Print speed

25/30 prints per minute

Printer language

Standard: PCL5e, PCL6, RPCS™
Option: Adobe® PostScript® 3™

Resolution

Maximum: 600 x 600dpi (2,400dpi equivalent x 600dpi with smoothing)

Interface

Standard: USB 2.0 Ethernet 10 base-T/
100 base-TX
Option: Bi-directional IEEE1284
FireWire (IEEE1394)
Wireless LAN (IEEE802.11b)
Bluetooth

Memory

384MB + 20GB Hard disk drive

Network protocol

TCP/IP, IPX/SPX, SMB, AppleTalk

Supported environments

Windows® 95/98/Me/NT4.0/2000/XP/
Server 2003
Novell® NetWare® 3.12/3.2/4.1/4.11/5.0/
5.1/6/6.5
UNIX Sun® Solaris 2.6/7/8/9/10, HP-UX
10.x/11.x/11iv1/11i
SCO OpenServer 5.0.6/5.0.7
RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise
IBM® AIX v4.3/5L v5.1/5L v5.2/5.3
Macintosh 8.6 or later (OS X Classic)
Macintosh X v10.1 or later (native mode)

Copier

Copying process

Twin laser beam scanning & electro-
photographic printing

CPU

RM7035C-466 466MHz

Copy speed

25/30 copies per minute

Resolution

600dpi

Multiple copy

Up to 999

Warm up time

12 seconds

First output speed

4.4 seconds

Zoom

25 - 400% (in 1% steps)

Memory

Standard: 128MB
Maximum: 384MB + 20GB Hard disk drive

Paper input capacity

Standard: 2 x 500-sheet trays
Maximum: 3,100 sheets

Paper output capacity

Standard: 500 sheets
Maximum: 1,625 sheets

Paper size

A6 - A3

Paper weight

Paper tray 1: 60 - 105g/m²
Paper tray 2/bypass tray: 52 - 157g/m²
Duplex tray: 64 - 105g/m²

Dimensions (W x D x H)

550 x 604 x 980mm

Weight

Less than 62kg

Power source

220 - 240V, 50/60Hz

Power consumption

Operation: Maximum 1.32kW
Energy saver mode: Less than 120W
Auto Off mode: Less than 7.5W

Scanner (Option)

Scan speed

Maximum 52 originals per minute
(MH, A4/LEF)

Resolution

Maximum 600dpi (TWIN: 1,200dpi)

Original size

A5 - A3

Output formats

PDF/JPEG/TIFF

Bundled drivers

Network TWIN

Scan-to-email

SMTP, TCP/IP

Destination addresses

Maximum 500 per job

Stored destination addresses

Maximum 2,000

Address book

Via LDAP or locally on Hard disk drive

Scan to folder

SMB, FTP, NCP protocol
(with log-in security)

Destination

Maximum 50 folders per job

Fax (Option)

Circuit

PSTN, PBX

Compatibility

ITU-T (CCITT) G3
ITU-T (T.37) Internet Fax
ITU-T (T.38) IP Fax

Modem speed

Maximum 33.6kbps

Resolution

Standard/detail: 200 x 100/200dpi
Maximum: 400 x 400dpi (option)

Compression method

MH, MR, MMR, JBIG

Scanning speed

Less than 0.56 seconds (200 x 100dpi,
A4 SEF), ARDF

Memory capacity

Standard: 12MB
Maximum: 44MB

Memory backup

Yes

Software

SmartDeviceMonitor™¹
Web SmartDeviceMonitor™¹
Web Image Monitor¹
DeskTopBinder™ Lite¹

¹ Bundled with printer/scanner option

Other Options

- Platen cover
- 50-sheet Automatic Reverse Document Feeder
- 100-sheet multi-bypass tray
- 2 x 500-sheet paper trays
- 2,000-sheet large capacity tray
- 125-sheet one-bin tray
- 500-sheet finisher [1 position stapling]
- 1,000-sheet multi-tray finisher [3 position stapling]
- Shift sort tray
- Duplex unit
- 20GB Hard disk drive
- 2nd Super G3 port
- Data Overwrite Security Unit
- Copy Data Security Unit
- File Format Converter
- User Account Enhance Unit
- Browser Unit
- VM Card
- Key Counter Bracket
- PI Board

Company management systems applied during the manufacturing of all Gestetner products conform to ISO9001 quality and ISO14001 environmental management standards.

As an ENERGY STAR Program Participant, Gestetner has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

We reserve the right to make amendments to the technical specifications and external appearance of this equipment. Please note that the full range of options shown in this publication may not always be available. All brand and product names are recognized and hereby acknowledged, as registered trademarks of their respective owners.



6053723006680

Gestetner

Part of the NRG group

www.gestetner.com

